

BOROUGHS OF RUMSON & FAIR HAVEN

Division of Fire Safety & Fire Prevention 80 East River Road Rumson, New Jersey 07760 732-842-3022 Office 732-842-0961 Fax



Email: Mhawley@rumsonnj.gov Mhawley@fhboro.net

N.J. Uniform Fire Code Update

N.J.A.C. 5:70-4.19

Smoke alarms for one- and two-family dwellings; carbon monoxide alarms; and portable fire extinguishers

Smoke Alarms:

- (a) In one- and two-family or attached single family dwellings subject to the requirements of N.J.A.C. 5:70-2.3, smoke alarms shall be installed as follows:
 - 1. On each level of the premises, and
 - 2. Outside each sleeping area, in the vicinity of the bedrooms

One- and Two-family Dwelling Sub code (N.J. IRC/2015)

R314.1 General, Smoke Alarms shall comply with NFPA 72 and Section R341

R314.3 Location, Smoke Alarms shall be installed in the following locations,

- 1. In each sleeping room
- (b) The smoke alarms required in (a) above shall be located and maintained in accordance with NFPA 72
 - 1. The alarms shall not be required to be interconnected.
- (c) Ten-year sealed battery-powered single station smoke alarms shall be installed in accordance with ANSI/UL 217. However, A/C-powered single of multiple-station smoke alarms shall not be replaced with battery-powered smoke alarms.
 - 1. A/C-powered smoke alarms shall be accepted as meeting the requirements of this section

Carbon Monoxide Alarms:

- (d) Carbon monoxide alarms shall be installed in all dwelling units in buildings in one- and two-family or attached single family dwellings, *except for units in buildings that do not contain a fuel-burning device or have an attached garage*, as follows:
 - 1. Single station carbon monoxide alarms shall be installed and maintained in the immediate vicinity of the sleeping area(s)
 - 2. Carbon monoxide alarms may be battery-operated, hard-wired or of the plug-in type and shall be listed and labeled in accordance with UL-2034 and shall be installed in accordance with the requirements of this section and NFPA-720.

Secondary Power Source:

(e) P.L.2025, c.19 requirements apply to one- or two-family and attached single family dwellings upon a change of occupancy and are as follows;



BOROUGHS OF RUMSON & FAIR HAVEN

Division of Fire Safety & Fire Prevention 80 East River Road Rumson, New Jersey 07760 732-842-3022 Office 732-842-0961 Fax



Email: Mhawley@rumsonnj.gov Mhawley@fhboro.net

- 1. A structure used or intended for use for residential purposes must have a label installed within 18 inches of the main electrical panel and electrical meter warning of the dangers associated with secondary power sources.
- 2. Secondary power sources include:
 - i. Permanently installed combustion generators,
 - ii. Solar panels,
 - iii. Battery storage systems, or
 - iv. Any other supplemental source of electrical energy to the primary power supply
- 3. Label must be marked with wording similar to "CAUTION: MULTIPLE SOURCES OF POWER."
- 4. Label may not be hand written
- 5. Label compliant with ANSI Z535.4 will meet the requirements of this law.

Fire Extinguishers (optional):

- (f) A portable fire extinguisher shall be installed in accordance with the following:
 - 1. The extinguisher shall be within 10 feet of the kitchen and located in the path of egress.
 - 2. The extinguisher shall be readily accessible and not obstructed from view.
 - 3. The extinguisher shall be mounted using the manufacturer's hanging bracket so the operating instructions are clearly visible.
 - 4. The extinguisher shall ne am approved listed and labeled type with a rating of 2A-10B:C and no more than 10 pounds.
 - 5. The owner's manual or written operating instructions shall be provided during inspection and left for the new occupant.
 - 6. The extinguisher shall be serviced and tagged by a certified Fire Safety Contractor within the past 12 months or the seller/landlord must have a receipt for a recently purchased extinguisher.
 - 7. The top of the extinguisher shall not be mounted more than five feet above the floor.